

P 20



PVDF+CF

WEIGHT
1,6 kg

TEMPERATURE
-20°C +90°C

CE EAC

UK CA

PERFORMANCE

TECHNICAL DATA


Fluid connections	3/8" BSPP
Air connection	1/4" BSPP
Max. flow rate	20 lt/min
Max air pressure	7 bar
Max delivery head	70 m
Max suction lift dry	5 m
Max suction lift wet	9,8 m
Max solid passing	2,5 mm
Noise level	65 dB
Max viscosity	10.000 cps

Displacement per stroke **30 CC ~**

Displacement per stroke may vary based on suction condition, discharge head, air pressure and fluid type.

II 3/3 G Ex h IIC T4 Gc

II 3 D Ex h IIIB T135°C Dc X



Made in Italy

fluimac
pump solution


FLUIMAC S.r.l. - Via Breascia, 1 - 21049 - Tradate - VA - ITALY
info@fluimac.com - www.fluimac.com
tel. +39 0331 866688 - Fax +39 0331 864870
P.I./VAT 03259160129

ISO 9001
BUREAU VERITAS
Certification
ISO 9001:2008

P 20

COMPOSITION

MODEL	CASING	DIAPHRAGM	BALLS	SEATS	GASKET	CONNECTIONS	ATEX	PORTS
P0020	KC = PVDF+C F	HT = HYTREL+PTFE MT = SANTOPRENE+PTFE H = HYTREL	T=PTFE S=SS	K = PVDF S = SS	D = EPDM V = VITON N = NBR T = PTFE	1 = BSPP 5 = NPT A = BSPP with reinforce ring E = NPT with reinforce ring	- = ZONE 2	AB = STANDAR D



AVAILABLE CONNECTIONS


DELIVERY: B-D-S

SUCTION: A-C-T

PACKING DIMENSION

CARTON BOX: 24 x 21 x 12 cm

DIMENSIONS



Technical data are approximate and not binding for the manufacturer who reserves the right to change them without notice at any time.



FLUIMAC S.r.l. - Via Breascia, 1 - 21049 - Tradate - VA - ITALY
info@fluimac.com - www.fluimac.com
 tel. +39 0331 866688 - Fax +39 0331 864870
 P.I./VAT 03259160129

